

Reka Glue Guns Pneumatic



Hot-Melt Applicator TR 50.5



Subject to modifications

Fig. TR 50.5

Made in Germany

TR 50.5 Glue Gun – Best Gluing Results with comfortable Air Pressure Application and Comfort Locking

The all new TR 50.5 applies hot-melt glue granulate, pillows and even 43 mm sticks easily and precisely. With the innovative comfort locking refilling glue has never been that convenient. The hot glue is extracted with compressed air which enables the user easy operation and a continuous workflow.

Thanks to the electronic temperature regulation the TR 50.5 is ready to go within minutes and keeps the set temperature accurately to achieve the best gluing

result. Due to the stable temperature the glue is also protected from degenerating or coking. The temperature can be set from 170 to 190 °C. The TR 50.5 is well suited to work in dusty and demanding work environments and the 250 ml capacity is enough to make numerous bondings. Combined with the reka nozzle portfolio the TR 50.5 handles countless applications comfortably, powerful and professional.

Technical Data

	TR 50.5	
Article Number	5435 (230 V)	5204 (120 V)
Weight	1200 g	
Power Supply	230 V / 50 Hz	120 V / 60 Hz
Power Consumption	500 Watt (230 V)	400 Watt (120 V)
Current Consumption	2,2 A	3,3 A
Degree of protection	IP 30	
Class of protection	I	
Temperature control	electronic	
Temperature limitation	Temperature monitor	
Operating temperature	170 – 190 °C	
Consistency of temperature	± 2 °C	
Temperature indication	digital	
Heat-up time	approx. 3 – 10 min.	
Gross Tank Capacity	250 ml	
Conveying system	Air pressure	
Operating pressure	0,5 – 6 bar	
Length of electric cord	8,5 m	
Length of air tube	5 m	
Length of connection kit	3 m	
Recommended melts	Hot-melt granulate, pillows and 43mm sticks/slugs	

Accessories

- 1 # 3518 Footswitch
- 2 # 3746 Stationary equipment
- 3 # 5563 Premelter
- 4 # 2770 Stand for storing
- 5 # 3544 Balancer
- 6 # 3519 Cleaning Liquid Meltanova
- 7 # 3465 Nozzle Set M14 Professional
- 8 Inquire about our nozzle range

Reka Klebetechnik GmbH & Co. KG
Siemensstr. 6
DE-76344 Eggenstein
Telefon: +49 721 970 780
Telefax: +49 721 705 069
E-Mail: in-fo@reka-klebetechnik.de
Internet: www.reka-klebetechnik.de